

1/28




FIG. 1




FIG. 2

3/28




FIG.3

4/28




FIG.4




FIG.5

6/28




FIG.6

7/28




FIG.7

8/28




FIG. 8




FIG. 9



9/28




FIG.10




FIG.11

10/28




FIG.12

11/28




FIG.13

12/28

Q1	Q2	DATA
0	0	X
0	1	1
1	0	0
1	1	X

FIG.14




FIG.15

14/28




FIG.16




FIG.17

15/28




FIG.18

[SYRI-UWBsystem (X3) Freq-Conversion Check]




FIG. 19

# UPE1: IMAGE REJECTION FILTER FOR PREVENTING RESTORATION AFTER UP-CONVERSION

MIX1+SBC3: UP CONVERTER (LOCAL OSCILLATOR FREQUENCY=5GHZ, CONVERSION LOSS=0dB)

**BP61: BAND PASS FILTER FOR PICKING OUT ONLY UPPER SIDE BAND**

MIX2+SPC4: DOWN CONVERTER (LOCAL OSCILLATOR FREQUENCY=5GHZ, CONVERSION LOSS=0dB)

LPF2: LOW PASS FILTER FOR PICKING OUT ONLY LOWER SIDE BAND

PWR1+SRC2: NOISE ADDER (V\_NOISE=0mV→UNUSED)






FIG.20

18/28




FIG.21

19/28




FIG. 22

20/28




FIG. 23




FIG.24




FIG.25




FIG.26




FIG.27






FIG.28

26/28




FIG. 29

27/28




FIG.30

28/28




FIG.31